


# LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 132.92 lm/W			
MODEL:FEL-D-40-V04-RZ-F-480		Imax(cd)	2069	S/MH(C0/180)	1.23
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	1.22
RATED VOLTAGE(V)	480	TOTAL FLUX(lm)	5258.0	$\eta$ UP,DN(C0-180)	0.0,50.6
NOMINAL FLUX(lm)	5258.04	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,49.4
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	480	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	2029	2034	2034	2031	2028	2023	2023	2022	0- 10	195.5	195.5	3.72,3.72
20	1908	1919	1916	1912	1905	1899	1900	1898	10- 20	557.8	753.2	14.3,14.3
30	1709	1721	1717	1713	1703	1693	1693	1698	20- 30	836.4	1590	30.2,30.2
40	1436	1447	1445	1436	1425	1414	1411	1423	30- 40	985.1	2575	49,49
50	1106	1120	1119	1107	1095	1082	1082	1093	40- 50	978.8	3553	67.6,67.6
60	751.6	767.5	767.9	753.4	743.8	727.9	728.2	738.4	50- 60	826.4	4380	83.3,83.3
70	409.6	426.7	425.5	415.6	402.8	387.7	387.9	395.7	60- 70	567.3	4947	94.1,94.1
80	121.9	134.7	132.6	129.0	115.5	104.2	104.9	107.8	70- 80	269.7	5217	99.2,99.2
90	1.914	2.063	2.101	1.946	1.532	1.530	1.530	1.530	80- 90	41.31	5258	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 3074.5 lm

%lum = 58.5%

%lamp = 58.5%

Conical surface Flux(120deg): 4379.8 lm

%lum = 83.3%


%lamp = 83.3%

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3049	3960
80	7021	7634
75	9917	10417
70	11977	12440
65	13616	14022
60	15032	15359
55	16224	16474
50	17210	17411
45	18055	18204


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.05	1.01	.98	1.03	.99	.96	.99	.96	.93	.95	.93	.90	.91	.89	.88	.86
2.0	.92	.86	.81	.91	.85	.80	.87	.82	.78	.84	.80	.76	.81	.77	.74	.72
3.0	.82	.74	.68	.80	.73	.67	.77	.71	.66	.74	.69	.65	.72	.67	.64	.62
4.0	.73	.64	.58	.71	.63	.57	.69	.62	.57	.67	.61	.56	.64	.59	.55	.53
5.0	.65	.56	.50	.64	.56	.50	.62	.55	.49	.60	.54	.49	.58	.53	.48	.46
6.0	.59	.50	.44	.58	.50	.44	.56	.49	.43	.54	.48	.43	.53	.47	.43	.41
7.0	.53	.45	.39	.53	.44	.39	.51	.44	.38	.50	.43	.38	.48	.42	.38	.36
8.0	.49	.40	.35	.48	.40	.35	.47	.40	.34	.46	.39	.34	.44	.38	.34	.32
9.0	.45	.37	.31	.44	.37	.31	.43	.36	.31	.42	.36	.31	.41	.35	.31	.29
10.0	.41	.34	.28	.41	.33	.28	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:04 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### WEC AND CCEC

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.283	.161	.051	.276	.158	.050	.263	.151	.048	.251	.145	.046	.240	.139	.045		
2.0	.272	.149	.046	.266	.147	.045	.255	.142	.044	.244	.137	.043	.234	.132	.042		
3.0	.255	.136	.041	.250	.134	.040	.240	.130	.039	.230	.126	.039	.221	.123	.038		
4.0	.238	.123	.036	.233	.122	.036	.224	.119	.035	.215	.116	.035	.208	.113	.034		
5.0	.221	.113	.033	.217	.111	.032	.209	.109	.032	.201	.106	.032	.195	.104	.031		
6.0	.206	.103	.030	.202	.102	.029	.195	.100	.029	.189	.098	.029	.182	.096	.029		
7.0	.193	.095	.027	.189	.094	.027	.183	.093	.027	.177	.091	.026	.171	.089	.026		
8.0	.181	.088	.025	.178	.087	.025	.172	.086	.025	.167	.084	.024	.161	.083	.024		
9.0	.170	.082	.023	.167	.081	.023	.162	.080	.023	.157	.079	.023	.153	.077	.022		
10.0	.160	.077	.021	.158	.076	.021	.153	.075	.021	.149	.074	.021	.144	.073	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.136	.153	.134	.117	.104	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.145	.114	.087	.100	.079	.061	.057	.046	.035	.018	.015	.012	
3.0	.162	.114	.076	.139	.099	.066	.095	.068	.046	.055	.040	.027	.018	.013	.009	
4.0	.154	.101	.060	.132	.087	.052	.091	.061	.037	.053	.036	.022	.017	.012	.007	
5.0	.147	.090	.049	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006	
6.0	.140	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.016	.010	.005	
7.0	.133	.075	.034	.114	.065	.030	.079	.045	.021	.046	.027	.013	.015	.009	.004	
8.0	.127	.069	.029	.109	.060	.026	.076	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.104	.056	.022	.072	.039	.016	.042	.023	.009	.014	.008	.003	
10.0	.115	.060	.023	.100	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm										
NAME: LED Explosion-proof Flood Light					TYPE:Floodlight			WEIGHT:N/A		
SPEC.:40W/Lumileds 5050/5000K					DIM.: 265*265*150mm			SERIAL No.:N/A		
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.7	18.2	17.0	18.4	18.6	16.8	18.3	17.1	18.5	18.7
3H	17.9	19.2	18.2	19.5	19.7	18.0	19.4	18.3	19.6	19.8
4H	18.3	19.5	18.6	19.8	20.0	18.4	19.7	18.7	19.9	20.2
6H	18.5	19.7	18.8	19.9	20.2	18.6	19.8	18.9	20.1	20.4
8H	18.5	19.6	18.8	19.9	20.2	18.6	19.8	19.0	20.1	20.4
12H	18.4	19.6	18.8	19.8	20.1	18.6	19.7	19.0	20.0	20.3
4H 2H	17.2	18.5	17.6	18.8	19.0	17.3	18.6	17.6	18.8	19.1
3H	18.6	19.7	18.9	20.0	20.3	18.7	19.8	19.0	20.1	20.4
4H	19.1	20.1	19.4	20.4	20.7	19.2	20.2	19.6	20.5	20.9
6H	19.3	20.2	19.7	20.6	20.9	19.5	20.4	19.9	20.7	21.1
8H	19.4	20.2	19.8	20.6	21.0	19.5	20.4	19.9	20.7	21.1
12H	19.4	20.1	19.8	20.5	20.9	19.5	20.3	20.0	20.7	21.1
8H 4H	19.2	20.1	19.6	20.4	20.8	19.3	20.2	19.8	20.5	20.9
6H	19.6	20.3	20.0	20.7	21.1	19.7	20.4	20.2	20.8	21.2
8H	19.7	20.3	20.1	20.7	21.2	19.8	20.4	20.3	20.9	21.3
12H	19.7	20.2	20.2	20.7	21.1	19.9	20.4	20.3	20.8	21.3
12H 4H	19.2	20.0	19.6	20.4	20.8	19.3	20.1	19.8	20.5	20.9
6H	19.6	20.2	20.1	20.6	21.1	19.7	20.3	20.2	20.8	21.2
8H	19.7	20.2	20.2	20.7	21.1	19.9	20.4	20.3	20.8	21.3
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				
2.0H	+ 0.4 / - 0.4					+ 0.3 / - 0.4				

CIE Pub.117, 5258 lm Total Lamp Luminous Flux Correct ( $8\log(F/F_0) = 5.8$ )

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	60	49	42	59	48	42	58	48	42	35
0.80	70	59	52	69	59	52	67	58	51	45
1.00	79	68	61	77	67	61	75	69	60	53
1.25	86	76	69	84	75	69	82	74	68	61
1.50	90	81	75	89	80	74	86	79	73	66
2.00	97	89	83	95	88	82	92	86	81	73
2.50	101	93	88	99	92	87	95	89	85	77
3.00	104	97	92	102	96	91	98	93	89	81
4.00	107	102	98	105	101	97	101	97	94	85
5.00	110	105	102	107	103	100	103	100	97	88
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:04 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:3735 lm




**Note:**The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### LED Avg.L Report

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	13542
L_0~180 (75) av	9757
L_0~180 (85) av	2908
L_90~270 (65) av	13553
L_90~270 (75) av	9767
L_90~270 (85) av	2960
L_45 (65) av	13531
L_45 (75) av	9778
L_45 (85) av	2979

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: CL  
 Test Date: 04 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 6.010m [K=1.0000]  
 Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 04 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:479.84V I:0.0867A P:39.557W PF:0.9504 Freq:59.98Hz Lamp Flux:5258.04x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/5000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 04 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```