


# LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 123.57 lm/W			
MODEL:FEL-D-40-V04-RN-F-480		Imax(cd)	1975	S/MH(C0/180)	1.21
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	1.21
RATED VOLTAGE(V)	480	TOTAL FLUX(lm)	4945.1	$\eta$ UP,DN(C0-180)	0.0,51.0
NOMINAL FLUX(lm)	4945.06	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,49.0
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	480	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	1935	1942	1941	1936	1928	1923	1925	1929	0- 10	186.4	186.4	3.77,3.77
20	1813	1827	1825	1814	1801	1792	1796	1806	10- 20	530.3	716.8	14.5,14.5
30	1618	1636	1631	1620	1604	1590	1592	1604	20- 30	791.8	1509	30.5,30.5
40	1354	1373	1370	1353	1335	1319	1317	1334	30- 40	928.3	2437	49.3,49.3
50	1042	1062	1059	1043	1021	999.7	1000	1016	40- 50	918.2	3355	67.8,67.8
60	711.0	728.2	726.7	709.8	684.5	665.6	665.3	682.2	50- 60	771.8	4127	83.5,83.5
70	392.2	406.8	403.9	388.5	365.5	349.3	352.1	368.4	60- 70	528.2	4655	94.1,94.1
80	120.9	136.0	127.1	115.5	100.9	88.12	93.72	104.7	70- 80	251.1	4906	99.2,99.2
90	1.935	2.136	2.031	1.743	1.420	1.427	1.425	1.415	80- 90	38.79	4945	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 2906.3 lm

%lum = 58.8%

%lamp = 58.8%

Conical surface Flux(120deg): 4126.9 lm

%lum = 83.5%


%lamp = 83.5%

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3491	3809
80	6964	7317
75	9584	9915
70	11467	11809
65	12953	13285
60	14221	14533
55	15291	15584
50	16208	16475
45	17001	17243


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.05	1.01	.98	1.03	.99	.96	.99	.96	.93	.95	.93	.90	.91	.89	.88	.86
2.0	.93	.86	.81	.91	.85	.80	.87	.82	.78	.84	.80	.76	.81	.78	.75	.72
3.0	.82	.74	.68	.80	.73	.67	.77	.71	.66	.75	.69	.65	.72	.68	.64	.62
4.0	.73	.64	.58	.71	.64	.58	.69	.62	.57	.67	.61	.56	.65	.59	.55	.53
5.0	.65	.57	.50	.64	.56	.50	.62	.55	.49	.60	.54	.49	.58	.53	.48	.46
6.0	.59	.50	.44	.58	.50	.44	.56	.49	.43	.55	.48	.43	.53	.47	.43	.41
7.0	.54	.45	.39	.53	.45	.39	.51	.44	.39	.50	.43	.38	.48	.43	.38	.36
8.0	.49	.41	.35	.48	.40	.35	.47	.40	.35	.46	.39	.34	.45	.39	.34	.32
9.0	.45	.37	.32	.44	.37	.31	.43	.36	.31	.42	.36	.31	.41	.35	.31	.29
10.0	.42	.34	.29	.41	.34	.29	.40	.33	.28	.39	.33	.28	.38	.32	.28	.27



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:05 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### WEC AND CCEC

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.282	.161	.051	.275	.157	.050	.262	.150	.048	.250	.144	.046	.239	.139	.045		
2.0	.272	.149	.046	.265	.146	.045	.254	.141	.044	.243	.136	.043	.233	.132	.042		
3.0	.254	.135	.041	.249	.133	.040	.239	.129	.039	.230	.126	.039	.221	.122	.038		
4.0	.237	.123	.036	.232	.122	.036	.223	.118	.035	.215	.115	.035	.207	.113	.034		
5.0	.221	.112	.033	.216	.111	.032	.208	.109	.032	.201	.106	.032	.194	.104	.031		
6.0	.206	.103	.030	.202	.102	.029	.195	.100	.029	.188	.098	.029	.182	.096	.028		
7.0	.192	.095	.027	.189	.094	.027	.183	.092	.027	.177	.091	.026	.171	.089	.026		
8.0	.180	.088	.025	.177	.087	.025	.172	.086	.024	.166	.084	.024	.161	.083	.024		
9.0	.169	.082	.023	.167	.081	.023	.162	.080	.023	.157	.079	.022	.152	.077	.022		
10.0	.160	.077	.021	.157	.076	.021	.153	.075	.021	.148	.074	.021	.144	.072	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.137	.153	.134	.118	.104	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.145	.114	.087	.100	.079	.061	.057	.046	.036	.018	.015	.012	
3.0	.161	.114	.076	.138	.099	.066	.095	.068	.047	.055	.040	.027	.018	.013	.009	
4.0	.154	.101	.060	.132	.087	.052	.091	.061	.037	.053	.036	.022	.017	.012	.007	
5.0	.147	.090	.049	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006	
6.0	.140	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.015	.010	.005	
7.0	.133	.075	.034	.114	.065	.030	.079	.045	.021	.046	.027	.013	.015	.009	.004	
8.0	.127	.069	.029	.109	.060	.026	.075	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.104	.056	.022	.072	.039	.016	.042	.023	.010	.014	.008	.003	
10.0	.115	.060	.023	.099	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm										
NAME: LED Explosion-proof Flood Light					TYPE:Floodlight			WEIGHT:N/A		
SPEC.:40W/Lumileds 5050/3000K					DIM.: 265*265*150mm			SERIAL No.:N/A		
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.8	18.2	17.0	18.4	18.6	16.9	18.3	17.1	18.5	18.7
3H	18.0	19.3	18.3	19.5	19.8	18.1	19.4	18.4	19.6	19.9
4H	18.4	19.6	18.7	19.9	20.1	18.5	19.8	18.8	20.0	20.3
6H	18.6	19.8	18.9	20.0	20.3	18.7	19.9	19.0	20.2	20.4
8H	18.6	19.7	18.9	20.0	20.3	18.7	19.9	19.1	20.2	20.4
12H	18.6	19.7	18.9	20.0	20.3	18.7	19.8	19.0	20.1	20.4
4H 2H	17.3	18.6	17.6	18.8	19.1	17.4	18.6	17.7	18.9	19.1
3H	18.7	19.8	19.0	20.1	20.4	18.7	19.9	19.1	20.1	20.4
4H	19.2	20.2	19.5	20.5	20.8	19.3	20.3	19.6	20.6	20.9
6H	19.5	20.4	19.9	20.7	21.1	19.6	20.5	20.0	20.8	21.2
8H	19.5	20.3	19.9	20.7	21.1	19.6	20.5	20.0	20.8	21.2
12H	19.5	20.3	19.9	20.7	21.1	19.6	20.4	20.1	20.8	21.2
8H 4H	19.4	20.2	19.8	20.5	20.9	19.4	20.3	19.9	20.6	21.0
6H	19.7	20.4	20.2	20.8	21.3	19.8	20.5	20.3	20.9	21.4
8H	19.8	20.4	20.3	20.9	21.3	19.9	20.6	20.4	21.0	21.4
12H	19.9	20.4	20.3	20.8	21.3	20.0	20.5	20.5	20.9	21.4
12H 4H	19.3	20.1	19.8	20.5	20.9	19.4	20.2	19.9	20.6	21.0
6H	19.8	20.4	20.2	20.8	21.2	19.9	20.5	20.3	20.9	21.3
8H	19.9	20.4	20.3	20.8	21.3	20.0	20.5	20.5	20.9	21.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4				

CIE Pub.117, 4945 lm Total Lamp Luminous Flux Correct ( $8\log(F/F_0) = 5.6$ )

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	60	49	42	59	49	42	58	48	42	36
0.80	70	59	52	69	59	52	68	58	52	45
1.00	79	68	61	77	68	61	75	69	60	54
1.25	86	76	69	84	75	69	82	74	68	61
1.50	90	81	75	89	80	74	86	79	73	66
2.00	97	89	83	95	88	82	92	86	81	73
2.50	101	94	88	99	92	87	95	90	85	77
3.00	104	98	92	102	96	91	98	93	89	81
4.00	108	102	98	105	101	97	101	97	94	85
5.00	110	105	102	107	103	100	103	100	97	88
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:05 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### ISOCANDELA DIAGRAM

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:3525 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### LED Avg.L Report

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	12630
L_0~180 (75) av	9097
L_0~180 (85) av	2746
L_90~270 (65) av	12593
L_90~270 (75) av	9075
L_90~270 (85) av	2797
L_45 (65) av	12602
L_45 (75) av	9103
L_45 (85) av	2820

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:05 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: CL  
 Test Date: 05 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 6.010m [K=1.0000]  
 Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 05 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:480.16V I:0.0876A P:40.020W PF:0.9515 Freq:59.98Hz Lamp Flux:4945.06x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/3000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 05 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```