


# LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 134.67 lm/W			
MODEL:FEL-D-40-V04-RL-F-480		Imax(cd)	2125	S/MH(C0/180)	1.22
NOMINAL POWER(W)	40	LOR(%)	100.0	S/MH(C90/270)	1.22
RATED VOLTAGE(V)	480	TOTAL FLUX(lm)	5357.7	$\eta$ UP,DN(C0-180)	0.0,50.7
NOMINAL FLUX(lm)	5357.69	CIE CLASS	DIRECT	$\eta$ UP,DN(C180-360)	0.0,49.3
LAMPS INSIDE	1	$\eta$ up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	480	$\eta$ down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

## ZONAL FLUX DIAGRAM

### ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum,lamp
10	2087	2090	2087	2083	2078	2077	2081	2083	0- 10	200.8	200.8	3.75,3.75
20	1963	1971	1964	1955	1946	1944	1949	1955	10- 20	572.6	773.4	14.4,14.4
30	1757	1767	1757	1744	1732	1724	1731	1741	20- 30	856.4	1630	30.4,30.4
40	1475	1482	1473	1457	1440	1431	1439	1455	30- 40	1005	2635	49.2,49.2
50	1138	1146	1136	1119	1099	1089	1099	1116	40- 50	995.5	3631	67.8,67.8
60	775.2	783.8	777.0	758.2	737.1	730.0	735.6	754.2	50- 60	837.7	4468	83.4,83.4
70	426.7	438.2	431.4	415.4	395.2	384.6	390.6	406.9	60- 70	573.9	5042	94.1,94.1
80	131.4	146.1	136.7	124.3	110.8	97.55	103.7	115.4	70- 80	273.2	5315	99.2,99.2
90	2.033	2.283	2.192	1.876	1.514	1.504	1.485	1.469	80- 90	42.30	5358	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 3143.9 lm

%lum = 58.7%

%lamp = 58.7%

Conical surface Flux(120deg): 4468.3 lm

%lum = 83.4%


%lamp = 83.4%

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:04 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### LUMINANCE LIMITATION CURVES

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	3760	4135
80	7567	7872
75	10415	10612
70	12475	12613
65	14109	14188
60	15505	15539
55	16684	16682
50	17700	17679
45	18544	18530


C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio			Coefficients of Utilization(CU)												
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	1.00
1.0	1.05	1.01	.98	1.03	.99	.96	.99	.96	.93	.95	.93	.90	.91	.89	.88	.86
2.0	.93	.86	.81	.91	.85	.80	.87	.82	.78	.84	.80	.76	.81	.78	.74	.72
3.0	.82	.74	.68	.80	.73	.67	.77	.71	.66	.75	.69	.65	.72	.68	.64	.62
4.0	.73	.64	.58	.71	.64	.57	.69	.62	.57	.67	.61	.56	.65	.59	.55	.53
5.0	.65	.57	.50	.64	.56	.50	.62	.55	.49	.60	.54	.49	.58	.53	.48	.46
6.0	.59	.50	.44	.58	.50	.44	.56	.49	.43	.54	.48	.43	.53	.47	.43	.41
7.0	.54	.45	.39	.53	.45	.39	.51	.44	.39	.50	.43	.38	.48	.43	.38	.36
8.0	.49	.41	.35	.48	.40	.35	.47	.40	.35	.46	.39	.34	.45	.39	.34	.32
9.0	.45	.37	.31	.44	.37	.31	.43	.36	.31	.42	.36	.31	.41	.35	.31	.29
10.0	.42	.34	.29	.41	.34	.29	.40	.33	.28	.39	.33	.28	.38	.32	.28	.26



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### WEC AND CCEC

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.283	.161	.051	.276	.157	.050	.263	.151	.048	.251	.145	.046	.239	.139	.045		
2.0	.272	.149	.046	.266	.146	.045	.254	.141	.044	.244	.137	.043	.234	.132	.042		
3.0	.255	.136	.041	.249	.134	.040	.239	.130	.039	.230	.126	.039	.221	.122	.038		
4.0	.237	.123	.036	.232	.122	.036	.223	.118	.035	.215	.115	.035	.207	.113	.034		
5.0	.221	.113	.033	.217	.111	.032	.209	.109	.032	.201	.106	.032	.194	.104	.031		
6.0	.206	.103	.030	.202	.102	.029	.195	.100	.029	.188	.098	.029	.182	.096	.028		
7.0	.192	.095	.027	.189	.094	.027	.183	.092	.027	.177	.091	.026	.171	.089	.026		
8.0	.180	.088	.025	.177	.087	.025	.172	.086	.024	.166	.084	.024	.161	.083	.024		
9.0	.169	.082	.023	.167	.081	.023	.162	.080	.023	.157	.079	.023	.152	.077	.022		
10.0	.160	.077	.021	.157	.076	.021	.153	.075	.021	.148	.074	.021	.144	.073	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.178	.156	.137	.153	.134	.117	.104	.092	.081	.060	.053	.047	.019	.017	.015	
2.0	.170	.132	.100	.145	.114	.087	.100	.079	.061	.057	.046	.035	.018	.015	.012	
3.0	.162	.114	.076	.138	.099	.066	.095	.068	.046	.055	.040	.027	.018	.013	.009	
4.0	.154	.101	.060	.132	.087	.052	.091	.061	.037	.053	.036	.022	.017	.012	.007	
5.0	.147	.090	.049	.126	.078	.042	.087	.055	.030	.050	.032	.018	.016	.010	.006	
6.0	.140	.082	.040	.120	.071	.035	.083	.050	.025	.048	.029	.015	.015	.010	.005	
7.0	.133	.075	.034	.114	.065	.030	.079	.045	.021	.046	.027	.013	.015	.009	.004	
8.0	.127	.069	.029	.109	.060	.026	.075	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.104	.056	.022	.072	.039	.016	.042	.023	.010	.014	.008	.003	
10.0	.115	.060	.023	.099	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UGR(Unified Glare Rating) Table

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm										
NAME: LED Explosion-proof Flood Light					TYPE:Floodlight			WEIGHT:N/A		
SPEC.:40W/Lumileds 5050/4000K					DIM.: 265*265*150mm			SERIAL No.:N/A		
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	16.8	18.2	17.1	18.4	18.6	16.8	18.3	17.1	18.5	18.7
3H	18.0	19.3	18.3	19.5	19.8	18.0	19.3	18.3	19.6	19.8
4H	18.4	19.6	18.7	19.9	20.1	18.4	19.7	18.7	19.9	20.2
6H	18.6	19.8	18.9	20.0	20.3	18.6	19.8	18.9	20.1	20.4
8H	18.6	19.7	18.9	20.0	20.3	18.6	19.8	19.0	20.1	20.4
12H	18.6	19.7	18.9	20.0	20.3	18.6	19.7	19.0	20.0	20.3
4H 2H	17.3	18.6	17.6	18.8	19.1	17.3	18.6	17.6	18.8	19.1
3H	18.7	19.8	19.0	20.1	20.4	18.7	19.8	19.0	20.1	20.4
4H	19.2	20.2	19.5	20.5	20.8	19.2	20.2	19.6	20.5	20.9
6H	19.5	20.4	19.9	20.7	21.1	19.5	20.4	19.9	20.8	21.1
8H	19.5	20.3	19.9	20.7	21.1	19.6	20.4	20.0	20.8	21.1
12H	19.5	20.3	19.9	20.7	21.1	19.6	20.3	20.0	20.7	21.1
8H 4H	19.3	20.2	19.8	20.5	20.9	19.4	20.2	19.8	20.6	21.0
6H	19.7	20.4	20.2	20.8	21.2	19.8	20.5	20.2	20.9	21.3
8H	19.8	20.4	20.3	20.9	21.3	19.9	20.5	20.3	20.9	21.4
12H	19.9	20.4	20.3	20.8	21.3	19.9	20.4	20.4	20.9	21.4
12H 4H	19.3	20.1	19.8	20.5	20.9	19.4	20.1	19.8	20.5	20.9
6H	19.7	20.4	20.2	20.8	21.2	19.8	20.4	20.3	20.8	21.3
8H	19.9	20.4	20.3	20.8	21.3	19.9	20.4	20.4	20.9	21.4
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3				
1.5H	+ 0.2 / - 0.4					+ 0.2 / - 0.4				
2.0H	+ 0.3 / - 0.4					+ 0.3 / - 0.4				

CIE Pub.117, 5358 lm Total Lamp Luminous Flux Correct ( $8\log(F/F_0) = 5.8$ )

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### UTILIZATION FACTORS TABLE

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	60	49	42	59	49	42	58	48	42	36
0.80	70	59	52	69	59	52	67	58	52	45
1.00	79	68	61	77	68	61	75	69	60	54
1.25	86	76	69	84	75	69	82	74	68	61
1.50	90	81	75	89	80	74	86	79	73	66
2.00	97	89	83	95	88	82	92	86	81	73
2.50	101	93	88	99	92	87	95	90	85	77
3.00	104	98	92	102	96	91	98	93	89	81
4.00	108	102	98	105	101	97	101	97	94	85
5.00	110	105	102	107	103	100	103	100	97	88
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNM = 1.25		

C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:04 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

# ISOCANDELA DIAGRAM

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018


γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:



### AAI Figure

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:3815 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### ISOLUX DIAGRAM

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature:25.3DEG  
 Operators:CL  
 Test Date:04 December 2018

γ Range: 0 - 90DEG  
 γ Interval: 1.0DEG  
 Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity:65.0%  
 Test Distance:6.010m [K=1.0000]  
 Remarks:

### LED Avg.L Report

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	13685
L_0~180 (75) av	9899
L_0~180 (85) av	3028
L_90~270 (65) av	13693
L_90~270 (75) av	9880
L_90~270 (85) av	3028
L_45 (65) av	13696
L_45 (75) av	9902
L_45 (85) av	3060

Standard: GB/T 29293-2012

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature:25.3DEG  
Operators:CL  
Test Date:04 December 2018

γ Range: 0 - 90DEG  
γ Interval: 1.0DEG  
Test System:EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
Humidity:65.0%  
Test Distance:6.010m [K=1.0000]  
Remarks:

### Planar Illuminance Curve



C Range: 0 - 360DEG  
 C Interval: 15.0DEG  
 Test Speed: HIGH  
 Temperature: 25.3DEG  
 Operators: CL  
 Test Date: 04 December 2018

$\gamma$  Range: 0 - 90DEG  
 $\gamma$  Interval: 1.0DEG  
 Test System: EVERFINE GO-2000A\_V1 SYSTEM V2.0.366  
 Humidity: 65.0%  
 Test Distance: 6.010m [K=1.0000]  
 Remarks:

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 04 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```

## LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:480.20V I:0.0871A P:39.784W PF:0.9508 Freq:59.98Hz Lamp Flux:5357.69x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:40W/Lumileds 5050/4000K	DIM.: 265*265*150mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

C Range: 0 - 360DEG  
C Interval: 15.0DEG  
Test Speed: HIGH  
Temperature: 25.3DEG  
Operators: CL  
Test Date: 04 December 2018

```

γ Range: 0 - 90DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

```