


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

DATA OF LAMP		PHOTOMETRIC DATA Eff: 117.11 lm/W			
MODEL	FEL-I-80-3000K-透明	Imax(cd)	3695	S/MH(C0/180)	1.26
NOMINAL POWER(W)	80	LOR(%)	100.0	S/MH(C90/270)	1.32
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	9546.1	η UP,DN(C0-180)	0.0,46.2
NOMINAL FLUX(lm)	9546.14	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,53.8
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:

γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	3649	3616	3612	3600	3630	3654	3686	3668	0- 10	349.6	349.6	3.66,3.66
20	3481	3417	3394	3384	3441	3504	3564	3530	10- 20	1006	1356	14.2,14.2
30	3187	3096	3052	3053	3128	3237	3303	3276	20- 30	1533	2889	30.3,30.3
40	2760	2654	2601	2591	2676	2836	2916	2896	30- 40	1854	4743	49.7,49.7
50	2219	2086	2027	2010	2121	2290	2406	2363	40- 50	1907	6650	69.7,69.7
60	1562	1362	326.7	1304	1447	1638	1758	1725	50- 60	1604	8254	86.5,86.5
70	823.3	220.4	260.6	216.0	713.0	827.4	380.7	908.4	60- 70	943.1	9197	96.3,96.3
80	168.4	70.34	10.18	55.39	114.5	110.1	54.37	133.1	70- 80	323.0	9520	99.7,99.7
90	2.519	0	0	0	2.273	0	0	0	80- 90	26.34	9546	100,100
100									90-100			
110									100-110			
120									110-120			
130									120-130			
140									130-140			
150									140-150			
160									150-160			
170									160-170			
180									170-180			
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

Conical surface Flux(90deg): 5707.8 lm

%lum = 59.8%

%lamp = 59.8%

Conical surface Flux(120deg): 8253.7 lm

%lum = 86.5%


%lamp = 86.5%

H(β) Range:-90 - 90DEG
 H(β) Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:01 June 2018

V(B) Range:-80 - 80DEG
 V(B) Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



LUMINANCE cd/(m2)		
G (DEG)	C0/180	C90/270
85	2926	0
80	9698	586
75	18634	5232
70	24070	7620
65	28661	6949
60	31242	6534
55	33183	20520
50	34521	31538
45	35372	32724


H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.06	1.02	.99	1.04	1.00	.97	.00	.97	.94	.96	.93	.91	.92	.90	.89	.87
2.0	.94	.87	.82	.92	.86	.81	.88	.83	.79	.85	.81	.78	.82	.79	.76	.74
3.0	.83	.75	.69	.81	.74	.69	.78	.72	.67	.76	.70	.66	.73	.69	.65	.63
4.0	.74	.65	.59	.72	.65	.59	.70	.63	.58	.68	.62	.57	.65	.60	.56	.54
5.0	.66	.57	.51	.65	.57	.51	.63	.56	.50	.61	.55	.50	.59	.54	.49	.47
6.0	.60	.51	.45	.59	.50	.45	.57	.50	.44	.55	.49	.44	.54	.48	.43	.41
7.0	.54	.46	.40	.53	.45	.39	.52	.44	.39	.50	.44	.39	.49	.43	.39	.37
8.0	.49	.41	.35	.49	.41	.35	.47	.40	.35	.46	.40	.35	.45	.39	.35	.33
9.0	.45	.37	.32	.45	.37	.32	.44	.37	.32	.42	.36	.31	.41	.36	.31	.29
10.0	.42	.34	.29	.41	.34	.29	.40	.33	.29	.39	.33	.29	.38	.33	.28	.27



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

pcc	80%			70%			50%			30%			10%			0	
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
p _{fc}	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.269	.153	.048	.262	.149	.047	.249	.143	.046	.237	.137	.044	.226	.131	.042		
2.0	.262	.144	.044	.256	.141	.043	.245	.136	.042	.234	.131	.041	.225	.127	.040		
3.0	.248	.132	.040	.243	.130	.039	.233	.126	.038	.224	.122	.038	.215	.119	.037		
4.0	.233	.121	.036	.228	.119	.035	.219	.116	.035	.211	.113	.034	.203	.110	.034		
5.0	.218	.111	.032	.214	.110	.032	.206	.107	.032	.198	.105	.031	.191	.102	.031		
6.0	.204	.102	.029	.200	.101	.029	.193	.099	.029	.186	.097	.028	.180	.095	.028		
7.0	.191	.094	.027	.188	.094	.027	.181	.092	.026	.175	.090	.026	.170	.088	.026		
8.0	.179	.088	.025	.176	.087	.025	.171	.085	.024	.165	.084	.024	.160	.082	.024		
9.0	.169	.082	.023	.166	.081	.023	.161	.080	.023	.156	.078	.022	.152	.077	.022		
10.0	.159	.076	.021	.157	.076	.021	.152	.075	.021	.148	.073	.021	.144	.072	.021		

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.190	.190	.190	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.177	.156	.138	.152	.134	.118	.104	.092	.082	.060	.053	.048	.019	.017	.015	
2.0	.168	.132	.102	.144	.114	.088	.099	.079	.061	.057	.046	.036	.018	.015	.012	
3.0	.160	.114	.077	.137	.098	.067	.094	.068	.047	.054	.040	.028	.018	.013	.009	
4.0	.153	.101	.061	.131	.087	.053	.090	.061	.037	.052	.035	.022	.017	.012	.007	
5.0	.146	.090	.049	.125	.078	.043	.086	.054	.030	.050	.032	.018	.016	.010	.006	
6.0	.139	.082	.041	.119	.071	.035	.082	.049	.025	.048	.029	.015	.015	.010	.005	
7.0	.132	.075	.034	.114	.065	.030	.079	.045	.021	.046	.027	.013	.015	.009	.004	
8.0	.126	.069	.029	.109	.060	.026	.075	.042	.018	.044	.025	.011	.014	.008	.004	
9.0	.121	.064	.026	.104	.056	.023	.072	.039	.016	.042	.023	.010	.014	.008	.003	
10.0	.115	.060	.023	.099	.052	.020	.069	.037	.014	.040	.022	.008	.013	.007	.003	

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm										
NAME: LED Explosion-proof Flood Light					TYPE:Floodlight			WEIGHT:N/A		
SPEC.:80W					DIM.: 130*1200mm			SERIAL No.:N/A		
MFR.: NJZ Lighting Technology Co.,Ltd					SUR.:N/A			Shielding Angle:N/A		
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise					Viewed endwise				
x = 2H y = 2H	17.2	18.7	17.5	18.9	19.1	14.9	16.3	15.1	16.5	16.7
3H	18.4	19.8	18.7	20.0	20.2	14.9	16.3	15.2	16.5	16.7
4H	18.8	20.0	19.1	20.3	20.5	14.9	16.2	15.2	16.4	16.7
6H	18.9	20.0	19.2	20.3	20.6	14.9	16.0	15.2	16.3	16.6
8H	18.9	20.0	19.2	20.3	20.6	14.8	15.9	15.1	16.2	16.5
12H	18.8	19.9	19.2	20.2	20.5	14.8	15.8	15.1	16.1	16.4
4H 2H	17.4	18.7	17.7	18.9	19.2	15.3	16.6	15.6	16.8	17.1
3H	18.7	19.8	19.0	20.1	20.4	15.4	16.5	15.8	16.8	17.1
4H	19.1	20.1	19.5	20.4	20.7	15.5	16.5	15.9	16.8	17.1
6H	19.2	20.1	19.6	20.5	20.8	15.4	16.3	15.8	16.7	17.0
8H	19.2	20.0	19.6	20.4	20.8	15.4	16.2	15.8	16.6	16.9
12H	19.2	19.9	19.6	20.3	20.7	15.4	16.1	15.8	16.5	16.9
8H 4H	19.0	19.8	19.4	20.2	20.5	15.5	16.3	15.9	16.7	17.1
6H	19.2	19.8	19.6	20.2	20.6	15.5	16.2	15.9	16.6	17.0
8H	19.2	19.7	19.6	20.2	20.6	15.5	16.0	15.9	16.5	16.9
12H	19.2	19.6	19.6	20.1	20.6	15.4	15.9	15.9	16.4	16.8
12H 4H	18.9	19.7	19.4	20.1	20.5	15.5	16.2	15.9	16.6	17.0
6H	19.1	19.7	19.6	20.1	20.6	15.5	16.1	15.9	16.5	16.9
8H	19.1	19.6	19.6	20.1	20.5	15.4	15.9	15.9	16.4	16.8
Variations with the observer position at spacings:										
S = 1.0H	+ 0.2 / - 0.2					+ 0.6 / - 0.7				
1.5H	+ 0.3 / - 0.7					+ 0.7 / - 1.3				
2.0H	+ 0.4 / - 0.4					+ 2.0 / - 6.4				

CIE Pub.117, 9546 lm Total Lamp Luminous Flux Correct ($8\log(F/F_0) = 7.8$)

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:01 June 2018

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	60	49	42	59	48	42	58	48	42	35
0.80	70	59	52	69	59	52	68	58	52	45
1.00	79	69	62	78	68	62	76	70	61	55
1.25	86	77	70	85	76	70	82	75	69	62
1.50	91	82	76	90	81	76	87	80	74	67
2.00	98	90	85	96	89	84	93	87	82	75
2.50	101	95	89	99	93	88	96	91	86	79
3.00	105	98	94	102	97	93	99	94	90	82
4.00	108	103	99	106	101	98	102	98	95	87
5.00	110	106	102	108	104	101	103	100	98	89
ROOM INDEX	UF(total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNM = 1.25		

$H(\beta)$ Range:-90 - 90DEG
 $H(\beta)$ Interval: 1.0DEG
 Test Speed: HIGH
 Temperature:25.3DEG
 Operators:CL
 Test Date:01 June 2018

$V(B)$ Range:-80 - 80DEG
 $V(B)$ Interval: 5.0DEG
 Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
 Humidity:65.0%
 Test Distance:6.010m [K=1.0000]
 Remarks:

ISOCANDELA DIAGRAM

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A




H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

AAI Figure

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Flux out:7601 lm




Note:The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A


AvgL	cd/m2
L_0~180 (65) av	27256
L_0~180 (75) av	16538
L_0~180 (85) av	2181
L_90~270 (65) av	16125
L_90~270 (75) av	6819
L_90~270 (85) av	0
L_45 (65) av	22977
L_45 (75) av	9330
L_45 (85) av	852

Standard: GB/T 29293-2012

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

Planar Illuminance Curve



H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--1

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--2

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--3

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.05V I:0.6846A P:81.514W PF:0.9918 Freq:59.98Hz Lamp Flux:9546.14x1 lm		
NAME: LED Explosion-proof Flood Light	TYPE:Floodlight	WEIGHT:N/A
SPEC.:80W	DIM.: 130*1200mm	SERIAL No.:N/A
MFR.: NJZ Lighting Technology Co.,Ltd	SUR.:N/A	Shielding Angle:N/A

Table--4

UNIT: cd

[illegible]

H(β) Range:-90 - 90DEG
H(β) Interval: 1.0DEG
Test Speed: HIGH
Temperature:25.3DEG
Operators:CL
Test Date:01 June 2018

```
V(B) Range:-80 - 80DEG
V(B) Interval: 5.0DEG
Test System:EVERFINE GO-2000A_V1 SYSTEM V2.0.366
Humidity:65.0%
Test Distance:6.010m [K=1.0000]
Remarks:
```